







PCB LAYOUT



Nominal dimension Tolerances (mm)							
	0 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 180	over 180 to 250
	±0.25	±0.3	±0.35	±0.5	±0.7	±0.9	±1.0

REV	DESCRIPTION	DRW.	DATE
00.1	初版发行	C.W	2022.06.28

Notes/备注:

1. Electrical properties/电气特性
UL Standard/UL 标准

Use Group/应用组别	B	C	D
Rated Voltage/额定电压 (V)	300	/	300
Rated Current/额定电流 (A)	15	/	10
Withstanding voltage/工频耐电压	AC 1600V/1Min		

IEC Standard/IEC 标准

Rated Voltage/额定电压 (V): 320
Rated Current/额定电流 (A): 24


Overvoltage Category/过电压类别 /Pollution Degree/污染等级	II/2	III/2	III/3
Voltage/电压 (V)	400	320	250
Rated Impulse Voltage/冲击耐电压(KV)	4	4	4

2. Connection data/连接数据

Wire range/线径范围(AWG/mm²): 22~14/0.2~2.5
Stripping length/剥线长度(mm): 7~8
Wire tightening torque/导线扭矩(N.m): 0.6~0.8

3. Environmental safety/环境安全

Operating temperature/工作温度范围(°C): -40~+105
RoHS compliant/符合RoHS环保要求



Part No./料号说明:

F-25R-7.62-XXP-C

Poles/P数
02: 2Poles
03: 3Poles
...
16: 16Poles

4	COVER 盖板	PC	UL94 V-2
3	PIN HEADER 焊针	Copper Alloy	Sn Plated
2	SCREW 螺丝	Steel	M3/Zn Plated
1	HOUSING 主体	PA66	Black/UL94 V-0
ITEM	NAME OF PART	MATERIAL	NOTES

APP.	DATE:	PART NO:	
CHK.	DATE:	F-25R-7.62-XXP-C	
DRW. C.W	DATE: 2022.06.28	DARWING TYPE: Customer Drawing	
PROJECTION		UNITS: mm	SCALE: 2.5:1 SHEET/OF: 1/1
AINNEWELL 昆山艾尼维尔电子有限公司 KUN SHAN AINNEWELL ELECTRONICS CO.,LTD			