





(Without Cover)



PCB LAYOUT

Part No./料号说明:

F-55S-10.0-XXP-C

Poles/P数
02: 2Poles
03: 3Poles
...
22: 22Poles

REV	DESCRIPTION	DRW.	DATE
00	初版发行	C.W	2023.10.16

Notes/备注:

1. Electrical properties/电气特性

UL Standard/UL 标准

Use Group/应用组别	B	C	D
Rated Voltage/额定电压 (V)	300	150	300
Rated Current/额定电流 (A)	20	20	10
Withstanding voltage/工频耐电压	AC 1600V/1Min		

IEC Standard/IEC 标准

Rated Voltage/额定电压 (V): 600

Rated Current/额定电流 (A): 32

Overvoltage Category/过电压类别 /Pollution Degree/污染等级	II/2	III/2	III/3
Voltage/电压 (V)	1000	600	600
Rated Impulse Voltage/冲击耐电压(KV)	6	6	6

2. Connection data/连接数据

Wire range/线径范围(AWG/mm²): 22~12/0.2~4

Stripping length/剥线长度(mm): 9~10

Wire tightening torque/导线扭矩(N.m): 1.2

3. Environmental safety/环境安全

Operating temperature/工作温度范围(°C): -40~+105

RoHS compliant/符合RoHS环保要求

4	SOLDER PIN 端子	Copper Alloy	Sn Plated
3	SCREW 螺丝	Steel	M4/Ni Plated
2	COVER 透明盖板	PC	UL94 V-2
1	HOUSING 主体	PA66-GF	Black/UL94 V-0
ITEM	NAME OF PART	MATERIAL	NOTES

APP.	DATE:	PART NO.: F-55S-10.0-XXP-C	
CHK.	DATE:		
DRW. C.W	DATE: 2023.10.16	DARWING TYPE: Customer Drawing	
PROJECTION		UNITS: mm	SCALE: 2.5:1 SHEET/OF: 1/1
AINEWELL		昆山艾尼维尔电子有限公司 KUN SHAN AINEWELL ELECTRONICS CO.,LTD	